

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
1 April 2004 (01.04.2004)

PCT

(10) International Publication Number
WO 2004/028171 A1

(51) International Patent Classification⁷: H04Q 3/00, 7/38

(21) International Application Number:
PCT/FI2003/000679

(22) International Filing Date:
17 September 2003 (17.09.2003)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
20021664 18 September 2002 (18.09.2002) FI

(71) Applicant (for all designated States except US): NOKIA CORPORATION [FI/FI]; Keilalahdentie 4, FIN-02150 Espoo (FI).

(72) Inventors; and

(75) Inventors/Applicants (for US only): PUNAGANTI,

Murali [IN/FI]; Evästie 10 A 22, FIN-01360 Vantaa (FI).
MALU, Chand [IN/FI]; Rasinkatu 14 C 102, FIN-01360 Vantaa (FI).


(74) Agent: KOLSTER OY AB; Iso Roobertinkatu 23, P.O. Box 148, FIN-00121 Helsinki (FI).

(81) Designated States (national): AE, AG, AL, AM, AT (utility model), AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ (utility model), CZ, DE (utility model), DE, DK (utility model), DK, DM, DZ, EC, EE (utility model), EE, EG, ES, FI (utility model), FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK (utility model), SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (regional): ARIPO utility model (GH), ARIPO patent (GH), ARIPO utility model (GM), ARIPO

[Continued on next page]

(54) Title: USER-CONFIGURABLE CALL ANSWERING/REDIRECTION MECHANISM



(57) Abstract: Very flexible call management is achieved by a method for handling a call setup request (7-10, 7-22, ...) from an A party (A1 ... A9) to a B party (511). A reachability server (RS) receives (7-0) the B party's multiple simultaneous caller groups, profiles, redirection settings and associations thereof. Each time the B party's reachability changes, he indicates his current profile (7-20, 7-40, 7-50). Based on the call setup request, the server (RS) determines the A party's identity. Based on the A identity, one of the multiple simultaneous caller groups is determined. Then one of the multiple associations that corresponds to the determined caller group and the current B party is determined. Finally, the call setup request is processed according to the redirection setting of the determined association. The redirection settings may indicate a changed call mode, such as chatting, in case the B party is unable to take a voice call.

WO 2004/028171 A1